

ROLL

TENDER SPECIFICATION

Manufacturer information

ISOLGOMMA S.r.l.
Via Dell'Artigianato 24
36020 Albettono (VI)
Italia
www.isolgomma.com

Brand: **ROLL - roll with 86% SBR elastomer granules**

Product properties

Application:	impact sound insulation to be used below wet or dry screeds	
Impact sound improvement ΔL_w :	≥ 22 dB (measured acc. to EN 10140-3 with evaluation acc. EN 717-2)	
Consisting of:	SBR granules and fibres compacted with a latex binder to a backing made of a synthetic non-woven; VOC free; Long side with 40mm self-adhesive overlap	
Standard form of delivery, mats:	width	1.040 mm
	length	5.000 mm
Thickness:	5 mm	
Load range:	3.000 kg/m ²	
Dynamic stiffness s'_t :	≤ 21 MN/m ³	(measured acc. to EN 29052-1)
Compressibility c:	≤ 1.4 mm	(measured acc. to EN ISO 29770)
European Technical Assessment:	ETA-22/0045	

The impact sound insulation mat is to be laid butt-jointed and bonded together at the joints using suitable adhesive tape.

A European Technical Assessment (ETA) must be submitted for deviating products.

Offered product: ROLL from Getzner Werkstoffe GmbH or equal.

Quantity: m²
Sum: €