

# UPGREI

## TENDER SPECIFICATION

### Manufacturer information

ISOLGOMMA S.r.l.  
Via Dell'Artigianato 24  
36020 Albettono (VI)  
Italia  
www.isolgomma.com

Brand: **UPGREI - roll with 80% EPDM elastomer granules**

### Product properties

Application:	impact sound insulation to be used below wet or dry screeds	
Impact sound improvement $\Delta L_w$ :	$\geq 26$ dB (measured acc. to EN 10140-3 with evaluation acc. EN 717-2)	
Consisting of:	EPDM granules compacted with a latex binder to a backing made of a polyester fibre layer and a synthetic non-woven; VOC free; Long side with 40mm self-adhesive overlap	
Standard form of delivery, mats:	width	1.040 mm
	length	5.000 mm
Thickness:	10 mm	
Load range:	3.000 kg/m <sup>2</sup>	
Dynamic stiffness $s'_t$ :	$\leq 6$ MN/m <sup>3</sup>	(measured acc. to EN 29052-1)
Compressibility c:	$\leq 2.2$ mm	(measured acc. to EN ISO 29770)
European Technical Assessment:	ETA-18/0554	

The impact sound insulation mat is to be laid butt-jointed and bonded together at the joints using suitable adhesive tape.

A European Technical Assessment (ETA) must be submitted for deviating products.

Offered product: UPGREI from Getzner Werkstoffe GmbH or equal.

Quantity: ..... m<sup>2</sup>  
**Sum:** ..... €